



DATASHEET

Technical Specification

Alarm	
1	Lock - string tamper alarm
2	Swiping card alarm
3	Unlock alarm
4	Wrong password alarm
5	Geo - fence alarm
Dimension	210mmx130mmx45mm
Housing Material	Engineering plastics
Weight	800g (with standard accessories)
Built in battery	15000mAh rechargeable Li ion battery
Working temperature	,14+to +140 °f (-10 to + 60 °C)
Storage temperature	,-4to +158°F (-20 to + 70 ° C)
Relative humidity	,5 to 95 % noncondensing
Waterproof Grade	IP67
Sensitivity	Tracking & Nav - 167 dBm ; Cold start (aided);- 149 dBm; Reacquisition; 161 dBm
Charging	5V DC Form charger
GSM Frequency ;	Quad band (850,900,1800,1900)
Optional modems	UMTS900/2100, UMTS850/1900
Function	
Transmission mode	SMS,TCP,UDP,PPP,FTP,HTTP,SSL,MQTT
1 Data automatic upload	Time interval
Locating mode	GPS/QZSS L1 C /A, GLONASS
Vibration detecting	Built in 3G sensor
Unlock	Unlocking of the device can be done remotely using remote password /SMS/Rfid/Bluetooth
Wake up mode	call/SMS/Swiping card / vibration / lock string tamper / Bluetooth
Lock status monitoring mode	Real time monitoring

Thank You

JSD Electronics India

A-36 ,Sector- 67

Noida

For Clarification- bdm@jsdelectronics.co.in

Mobile- 9818997286